



W292S4498 Hillside Rd. Waukesha, WI 53189

262-896-6780 Fax 262-896-6756

Henry Extended Handguard Sight System - MI-H5XRS / MI-H4XRS / MI-H357XRS / MI-H3030XRS

It is recommended these parts are installed by a qualified gunsmith. ***Depending on your firearm, minor fitment may be required*** Midwest Industries is not responsible for parts damaged by not following these instructions. Please read the instructions and get familiar with these parts before proceeding with installation. We have included one extra front sight screw and one extra rear sight set screw just in case you need them. We have provided a small Allen wrench and Torx wrench for the rear sight installation. You will need a small screw driver for the front sight work. We have also provided Vibra-tite for the screws. We do not recommend the use of any other thread locker.

Instructions

1. Make sure your rifle is unloaded and pointed in a safe direction, Repeat this step.
2. Remove the factory handguard. Reassemble without factory handguard.
3. Remove factory iron sights, front and rear.
4. Slide MI Handguard onto rifle and seat the location tangs into the recess of the receiver.
5. Apply a drop of Vibra-tite to all installation screws.
6. While pulling handguard against lower handguard tang, install and tighten rear set screw so it makes contact with magazine tube. Do NOT torque this screw.
7. Finger tighten the front mounting side screws. Do NOT Torque.
8. Slide the tension block down the barrel and mag tube. These will sit directly in front of the handguard mounting screw. The set screw will go into the slot of the tension block. Run the set screw down until it just makes contact. One at a time, each side.
9. Included are special nuts that are used for the top 45-degree slots. Some rifles may need these for the included 5 slot M-LOK rail due to large barrels.
10. Proceed to mounting the top rail and sights with provided torx screws. Install finger tight. X Model 45/70 or 30-30 will have 4 screws. X Model Pistol caliber guns will have 5 screws.
11. Install the two shorter receiver screws with provided Vibra-tite. Do not tighten.
12. Set the ghost ring wedge on the base plate and install the longer two receiver screws (do not Vibra-tite them). Before tightening these screws, line up the windage marks in the back so the wedge is centered on the base.
13. Find the bag with your replacement MI front sight and degrease the two small screws.
14. Add a drop of Vibra-tite to each of the screws and install the MI front sight. These screws are very small - DO NOT OVER TIGHTEN THEM.
15. Turn in the side set screws until they make contact with the receiver screws. DO NOT OVERTIGHTEN. These are the locking Screws once the gun is zeroed.
16. Once all screws are in place, align upper rail to the handguard. Tighten all 6 forward handguard screws to 20in/lbs. Tighten receiver screws to 10in/lbs. The tension block screws only need light finger tension. Do not tighten the rear peep sight portion until the gun is properly zeroed.

Zeroing adjustments

The small set screws in the rear wedge portion are for locking your zero in. Do not install Vibra-tite on these small screws until you are at the range zeroing your gun. Back these small screws off so you can make adjustments but DO NOT FULLY REMOVE THEM. These screws are very small and could be lost. Once zeroed you can back them off just enough to expose some thread to add Vibra-tite to them and turn them back in to make contact. The aperture only has one set screw and will allow elevation in half turn adjustments. Turn the aperture counter-clockwise to raise bullet impact. Turn the aperture clockwise in the base to drop the bullet impact. Move the sight wedge to the left to move the bullet impact to the left. Move the sight wedge to the right to move the bullet impact to the right. Once zero is achieved, fully tighten the main sight wedge screws and set screws.