



W292S4498 Hillside Rd. Waukesha, WI 53189

262-896-6780 Fax 262-896-6756

Straight and Pistol Grip Lever Stock Instructions

MI-LS-MPG/MI-LS-MS/MI-LS-HPG/MI-LS-HS/MI-LS-WS/MI-LS-RS/MI-LS-RPG/MI-LS-SW

It is recommended these parts are installed by a qualified gunsmith. Fitting may be required

Midwest Industries is not responsible for parts damaged by not following these instructions. Please read the instructions and get familiar with these parts before proceeding with installation. If you have questions, please contact us via phone or email for assistance.

Instructions

1. Make sure your rifle is unloaded and pointed in a safe direction.
2. Repeat step 1.
3. Remove Factory Stock attachment bolt
4. Slide off factory stock
5. Slide on MI stock
6. Install and tighten factory attachment bolt
7. Please note* sling swivel stud is not tightened. This can be removed for use of QD swivel or Vibra-tite in place for permanent function



W292S4498 Hillside Rd. Waukesha, WI 53189

262-896-6780 Fax 262-896-6756

Straight and Pistol Grip Lever Stock Instructions

MI-LS-MPG/MI-LS-MS/MI-LS-HPG/MI-LS-HS/MI-LS-WS/MI-LS-RS/MI-LS-RPG/MI-LS-SW

It is recommended these parts are installed by a qualified gunsmith. Fitting may be required

Midwest Industries is not responsible for parts damaged by not following these instructions. Please read the instructions and get familiar with these parts before proceeding with installation. If you have questions, please contact us via phone or email for assistance.

Instructions

1. Make sure your rifle is unloaded and pointed in a safe direction.
2. Repeat step 1.
3. Remove Factory Stock attachment bolt
4. Slide off factory stock
5. Slide on MI stock
6. Install and tighten factory attachment bolt.
7. Please note* sling swivel stud is not tightened. This can be removed for use of QD swivel or Vibra-tite in place for permanent function