



W292S4498 Hillside Rd. Waukesha, WI 53189
262-896-6780 Fax 262-896-6756
www.midwestindustriesinc.com

Marlin Handguard Adaptor Install Instructions

PART # MI-MAR336A

For Marlin 336 30-30 rifles with barrel band

Have these parts installed by a qualified Marlin rifle gunsmith

*These handguards will not work for rifles equipped with a hand guard cap.

**Read and follow these instructions step by step.
MI is not responsible for lost or stripped hardware.**

1. Make sure your rifle is unloaded and work area is free of ammunition.
2. Repeat step 1.
3. Remove the front sight, front band, rear band, and forearm. Use caution because the magazine spring is under pressure in magazine tube.
4. Slide hand guard adaptor on barrel/magazine with front towards muzzle.
5. Reassemble front band and front sight, do not strip out the screws.
6. Apply a drop of vibratite VC3 to the hand guard adaptor screw threads.
7. Align hole for adaptor screw with notch in magazine tube and barrel.
8. Torque hand guard adaptor screw to 35 inch/pounds.
9. Slide the MI handguard onto your rifle and seat the location tangs into the recess of the receiver.
10. Visually align the holes in the hand guard with the threaded hole in the hand guard adaptor.
11. Follow instructions that came with MI M-Lok hand guard to complete install.

If you have any questions please bring the rifle to a competent gunsmith for completion.