



W292S4498 Hillside Rd. Waukesha, WI 53189

262-896-6780 Fax 262-896-6756

www.midwestindustriesinc.com

Ruger 10/22 Take-Down Chassis Installation Instructions

MI-1022-TDC

Please read all instructions step-by-step before proceeding to install the handguard.

(If instructions are not followed, your warranty is void. If you are not comfortable with this install please have the 10/22 Take Down Chassis installed by a qualified gunsmith.)

Before proceeding, make sure your firearm is pointed in a safe direction, magazine removed and chamber empty. Remove all ammunition and magazines from the workspace.

- 1.) Lock the bolt to the rear and face the muzzle away from you. Remove barrel assembly.
- 2.) Flip the Ruger 10/22 upside down and remove factory stock retaining screw and buttstock. DO NOT REUSE THE FACTORY SCREW.
- 3.) Install AR grip adaptor on bottom of Midwest Industries 10/22 Take-Down Chassis with threaded grip screw hole facing rearward, install the ¼-20x1.5" screw from the top and torque screw to 35 inch/pounds.
- 4.) Turn chassis upright and align the Midwest Industries Ruger 10/22 Chassis with the trigger guard on the 10/22 receiver assembly, make sure the safety is centered between safe and fire, put the rear of the receiver in first then cam the front down.
- 5.) Drop the provided 12-24x3/4 hex screw in the screw hole in the hole in front of the magazine well and tighten to 55 inch/pounds, securing receiver to chassis.
- 6.) Install customer supplied receiver extension, use standard castle nut to tension off rear of chassis. When aligned tighten 6/32 set screw to 15 inch/pounds to prevent rotation. Check receiver extension is aligned and tight so it doesn't rotate during use.
- 7.) Install AR style grip with provided grip screw/washer and torque grip screw to 45 inch/pounds.
- 8.) Install barrel on receiver and perform a function check to make sure the firearm is in good working condition and all parts were reinstalled correctly.

Modification or alteration to this part (to include custom coatings on the chassis) voids all factory warranties.

If you have any questions about the install please give us a call at:

262-896-6780